

ViewSonic VA220-H - LED monitor - Full HD (1080p) - 22"(VA220-H)

ViewSonic VA220-H - LED monitor - 22" - 1920 x 1080 Full HD (1080p) @ 100 Hz - VA - 250 cd/m² - 4000:1 - 1 ms - HDMI, VGA



Main Specifications

Product Description	ViewSonic VA220-H - LED monitor - Full HD (1080p) - 22"
Device Type	LED-backlit LCD monitor - 22"
Energy Label QR Code URL	https://eprel.ec.europa.eu/qr/1931473
Energy Class	Class E
Power Consumption (On mode)	15 W
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 (VGA: 75 Hz, HDMI: 100 Hz)
Pixel Pitch	0.249 mm
Brightness	250 cd/m ²
Contrast Ratio	4000:1 / 50000000:1 (dynamic)
Response Time	1 ms (MPRT)
Colour Support	16.7 million colours
Colour Gamut	72% NTSC, 104% sRGB
Input Connectors	HDMI, VGA
Display Position Adjustments	Tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH) - with stand	49.501 cm x 18.897 cm x 38.194 cm
Weight	2.5 kg
Compliant Standards	CB, CE/EMC, RoHS, ERP, REACH, WEEE, EAC, UkrSEPRO

Extended Specification

General

Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Label QR Code URL	https://eprel.ec.europa.eu/qr/1931473
Energy Class	Class E
Diagonal Size	22"

Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 (VGA: 75 Hz, HDMI: 100 Hz)
Pixel Pitch	0.249 mm
Brightness	250 cd/m ²
Contrast Ratio	4000:1 / 50000000:1 (dynamic)
Colour Support	16.7 million colours
Colour Gamut	72% NTSC, 104% sRGB
Response Time	1 ms (MPRT)
Vertical Refresh Rate	48 - 100 Hz
Horizontal Refresh Rate	30 - 120 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
Features	3-sided borderless, Flicker Free technology, Blue Light Filter technology, SuperClear Vertical Alignment panel technology, ViewSonic Eye ProTech, Eco Mode, True 8-bit, Variable refresh rate (VRR)
Dimensions (WxDxH)	49.501 cm x 18.897 cm x 38.194 cm - with stand
Weight	2.5 kg

Miscellaneous

Features	Security lock slot (cable lock sold separately), VESA interface support
Cables Included	1 x HDMI cable
Backlight Life	30,000 hours
Compliant Standards	CB, CE/EMC, RoHS, ERP, REACH, WEEE, EAC, UkrSEPRO
Security Slot Type	Kensington security slot

Power

Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	15 W
Power Consumption SDR (On mode)	15 kWh/1000h
Power Consumption (Typical)	20 Watt
Power Consumption (Max)	22 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption (Off Mode)	0.3 Watt

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 90% (non-condensing)

Connectivity

Interfaces	HDMI VGA
------------	------------

Dimensions & Weight

Dimensions & Weight Details	With stand - width: 49.501 cm - depth: 18.897 cm - height: 38.194 cm - weight: 2.5 kg Without stand - width: 49.501 cm - depth: 5.068 cm - height: 28.698 cm - weight: 2.1 kg
-----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dimensions & Weight (Shipping)

Shipping Width	55 cm
----------------	-------

Shipping Depth	10.6 cm
Shipping Height	38.2 cm
Shipping Weight	3.3 kg

Mechanical

Display Position Adjustments	Tilt
Tilt Angle	-3/+15
VESA Mounting Interface	75 x 75 mm

What's in the box

ViewSonic VA220-H
HDMI cable

Product data is provided by CNET, we do not warrant the accuracy and completeness of the material contained in this data sheet